Will control of the



OFFICE OF NAVAL RESEARCH

Research Contract N00014-87-K-0014

R&T Code 413a001

Technical Report No. 20

A STUDY OF THERMODYNAMIC PHASE STABILITY OF INTERMETALLIC THIN FILMS OF Pt₂Ga, PtGa AND PtGa₂ ON GALLIUM ARSENIDE

by

Young K. Kim, David K. Shuh, R. Stanley Williams, Larry P. Sadwick and Kang L. Wang

To be published in

Proc.Mat.Res.Soc. Spring Symp., San Diego, 1989

University of California, Los Angeles

†Department of Chemistry & Biochemistry and Solid State Science Center Los Angeles, CA 90024-1569

and

*Department of Electrical Engineering Los Angeles, CA 90024-1594

July 1, 1989



Reproduction in whole or part is permitted for any purpose of the United States Government.

This document has been approved for public release and sale; its distribution is unlimited

0, •	 	_		-			
	 		_		~-	~~	 DACE

SECURTY CLASSIFICATION OF THIS PAGE					
	REPORT DOCUM	MENTATION	PAGE		
1a REPORT SECURITY CLASSIFICATION UNCLASSIFIED		16 RESTRICTIVE N/A	MARKINGS		
2a SECURITY CLASSIFICATION AUTHORITY N/A			AVAILABILITY OF		
26 DECLASSIFICATION / DOWNGRADING SCHEDU 11/A	LE		ved for publi ibution unliπ		=;
4 PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5 MONITORING	ORGANIZATION RE	PORT NUMBE	ER(S)
N/A					
6a NAME OF PERFORMING ORGANIZATION The Regents of the University of California	6b OFFICE SYMBOL (If applicable)	1) ONE Pas	onitoring organi sadena - Admi exandria - Te	nistrativ	<i>r</i> e
6c. ADDRESS (City. State, and ZIP Code)		76 ADDRESS (CI	ty, State, and ZIP (ode)	
Office of Contracts & Grants A U C L A, 405 Hilgard Avenue Los Angeles, CA 90024	dministration	1) 1030 E. 2) 800 N.	Quincy St.,	et, Pasade Arlingtor	ena, CA 91106 n, VA 22217-5000
Ba. NAME OF FUNDING SPONSORING ORGANIZATION	Bb OFFICE SYMBOL (If applicable)		T INSTRUMENT IDE	NTIFICATION	NUMBER
Office of Naval Research BL ADDRESS (City, State, and ZIP Code)	ONR	10 SOURCE OF	FUNDING NUMBER	 	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
800 N. Quincy Street, 614A:DHF Arlington, VA 22217-5000		PROGRAM ELEMENT NO	PROJECT NO	TASK NO	WORK UNIT ACCESSION NO
11 TITLE (Include Security Classification)		<u> </u>	<u> </u>	l	
INTASSITITED. A study of ther	modynamic phase PtGa, on gallin		of intermetal	ic thin f	ilms of
12 PERSONAL AUTHOR(S) Young K. Kim, David K. Shuh,			D. Sadwick a	nd Kang I	Mang
13a TYPE OF REPORT Tech Rept #20 FROM 198			ORT (Year, Month, L 1989		
16 SUPPLEMENTARY NOTATION					
17. COSATI CODES	18 SUBJECT TERMS (C	ontinue on reven	se_if_necessary\and	identify by b	block number)
FIELD GROUP SUB-GROUP.	>epitaxial gro				=
· · · · · · · · · · · · · · · · · · ·	composition a		nermodynamic	control,	J17/12
19. ABSTRACT (Continue on reverse if necessary	and identify by block in	umber)		GALLI	IM ARSENIAE
Epitaxial thin films of three difference	ent Pt Ga intermetal				
beam epitaxy (MBE). The resultant fi					
ray two-theta diffraction. Both PtGa N_2 up to 450°C and 600°, respectively					
form phases with higher Ga concentra	tion.				
Sign Homes					
20 DISTR.BUTION AVAILABILITY OF ABSTRACT			ECURITY CLASSIFIC	ATION	
 ☑ UNCLASSIFIED/UNLIMITED ☐ SAME AS E 22a NAME OF RESPONSIBLE INDIVIDUAL 	RPT DTIC USERS	UNCLASS:	IFIED (Include Area Code) 22c OFFICE	SYMBOL
R. Stanley Williams	28 edition may be used un	(213) 825-		UCI	1

A STUDY OF THERMODYNAMIC PHASE STABILITY OF INTERMETALLIC THIN FILMS OF PLGa, PIGa AND PIGa, ON GALLIUM ARSENIDE

Young K. Kim*, David K. Shuh*, R. Stanley Williams*, Larry P. Sadwick** and Kang L. Wang**

- *Department of Chemistry and Biochemistry and Solid State Science Center, University of California, Los Angeles, California 90024-1569
- **Department of Electrical Engineering Device Research Laboratory, University of California, Los Angeles California 90024

ABSTRACT

Epitaxial thin films of three different Pt-Ga intermetallic compounds have been grown on GaAs by molecular beam epitaxy (MBE). The resultant films have been annealed at various temperatures and then examined using X-ray two-theta diffraction. Both PtGa₂ and PtGa thin films are chemically stable on GaAs under 1 atmosphere of N₂ up to 450°C and 600°C, respectively. Thin films of Pt₂Ga react with GaAs at temperatures as low as 200°C to form phases with higher Ga concentration.

Introduction

The interface chemistry of metal-semiconductor contacts plays an important role in controlling the electrical properties of Schottky barriers and Ohmic contacts [1]. Chemically stable contacts must be formed at the metal-semiconductor interface in order for electronic devices to survive processing procedures and operate reliably in harsh environment applications for long periods of time [2,3]. A possible solution for this interface problem would be to use a contact metal that can coexist with GaAs in bulk thermodynamic equilibrium. Such stable metals can be found by examining ternary phase diagrams, such as the Pt-Ga-As system, which was experimentally elucidated by Tsai et. al. [4] and is illustrated in Fig. 1. The existence of a pseudobinary tie-line between two compounds in the ternary phase diagram implies that the compounds will not react with each other in a closed system, i.e. the bulk compounds are in thermodynamic equilibrium with respect to each other. Therefore, from Fig. 1 it can be expected that PtGa and PtGa₂ will form stable contacts with GaAs but that Pt₂Ga will not. In the present study, these expectations are tested by investigating the phase composition of thin films of Pt₂Ga, PtGa and PtGa₂ on GaAs after annealing to various temperatures.

Film Growth

The Pt-Ga intermetallic films were grown in a MBE chamber with a base pressure of 2 x 10⁻¹⁰ torr and a deposition pressure of approximately 4 x 10⁻⁹ torr. The two inch GaAs substrates were introduced via a cryopumped load lock system and mounted on a modified manipulator equipped with radiative heating elements. The samples were cleaned in-situ by heating to a temperature of approximately 525°C. The platinum was evaporated using a Varian 3 KW electron beam evaporator and the gallium was obtained from a Knudsen cell constructed of a pyrolytic boron nitride (PBN) crucible with a tantalium heating element. The fluxes of platinum and gallium were initially tuned to the proper stoichiometry based on empirical knowledge. PtGa₂ can be visually identified by its characteristic golden color, since PtGa₂ is the only Pt-Ga phase that has a band structure similar to that of elemental gold [5]. Neither PtGa nor Pt₂Ga can be easily identified by color. The flux rate from the gallium source was stabilized by temperature control circuits that ensured a constant flux rate for each source power setting. Subsequent depositions have been controlled with a Leybold-Inficon IC-6000 crystal monitor system. To obtain single phase Pt-Ga intermetallic films, the flux ratio of gallium to platinium was adjusted to be slightly Ga rich. Co-evaporation of each Pt-Ga intermetallic proceeded with the substrate held at temperatures ranging from near room temperature to over 500°C at epilayer growth rates ranging from approximately 0.5 to 5 microns/hour.

Composition Analysis

XRD patterns of the films were taken on a Phillips X-ray powder diffractometer, which was interfaced to a microcomputer that controlled the scan rate and collected data at 0.1° intervals with a counting time of 10 seconds at each angle. The total time required for a complete scan (20 from 10° to 100°) was about 3 hours and the typical signal-to-noise ratio for a strong diffraction peak was 30 to 1. The d spacings of the PtGa₂ and Pt₂Ga thin films were checked against a reference tabulation [6] to ensure that they were identified correctly. As

no known PtGa JCPDS data exists, the known d-spacings of PtGa [7] were compared with values calculated from the diffraction pattern of the thin film and were found to agree closely. The thin films were annealed for twenty minutes in a quartz tube furnace under a nitrogen atmosphere for temperatures ranging from 100°C to 800° C. In this paper, we present XRD results of annealing studies of the Pt-Ga intermetallic single phase thin films. A complete characterization of these films, including Auger electron spectroscopy (AES) and X-ray photoemission spectroscopy (XPS), will be presented elsewhere [8].




Fig. 1. Solidus portion of the Pt-Ga-As ternary phase diagram at 25°C.

Results and discussion

The grown films were specular, both to the eye and by optical microscopy. Fig. 2 shows typical powder XRD patterns of the three types of intermetallic single phase Pt-Ga thin films grown on GaAs (001) in the as-deposited state. The PtGa and Pt₂Ga thin films have a dominant (210) and (112) reflection, respectively. The PtGa₂ thin films displayed roughly equal intensity (111), (220) and (311) reflections. This would seem to imply that the crystal quality of PtGa and Pt₂Ga thin films is better than that of PtGa₂ films in spite of larger lattice mismatches. XRD patterns of a sample of Pt₂Ga on GaAs annealed to 500°C are shown in Fig. 3. Even at 200°C, a new peak corresponding to the PtGa (210) reflection begins to appear at 20 = 41.4°. In the diffraction patterns of the film heated to high temperatures, new phases, such as PtGa₂ and PtAs₂, begin to form at 300°C and all peaks corresponding to the Pt₂Ga phase eventually disappeared at 500°C. According to the Pt-Ga-As ternary phase diagram, Pt₂Ga is expected to react with GaAs to produce PtAs₂ and PtGa, because there is no tie-line between Pt₂Ga and GaAs. However, annealing in an open system may cause As evaporation resulting from thermal decomposition of PtAs₂ and GaAs. With further loss of As, other Pt-Ga intermetallic compounds, such as PtGa₂ and Pt₃Ga₇, may be produced. This prediction agrees very well with the experimental results; all the peaks correspond to PtGa, PtGa₂, Pt₃Ga₇ and PtAs₂ in the diffraction pattern of the Pt₂Ga thin films on GaAs annealed to 500°C.

Fig. 4 shows XRD patterns of PtGa on a GaAs sample in the as-deposited state and after annealing at various temperatures for 20 minutes each. The diffraction pattern of the PtGa film annealed to 200°C shows that a small peak corresponding to Pt₂Ga (112) beside the PtGa (210) disappeared and the other PtGa peaks became sharper and more intense. This implies that a small amount of unstable Pt₂Ga phase in the PtGa thin film reacted with extra Ga in the film or with the substrate. Annealing improves the crystallinity of the PtGa

A-1

Codes

/or




Fig. 2. XRD patterns of the three types of intermetallic single phase Pt-Ga thin films grown on GaAs (100) in the as-deposited state: (a) as-deposited Pt₂Ga on GaAs; (b) as-deposited PtGa on GaAs; (c) as-deposited PtGa₂ on GaAs.

film, since the signal-to-background ratio in the XRD patterns begins to increase as annealing temperature goes up. The diffraction patterns for the PtGa film annealed from 300°C to 600°C were essentially identical, but the signal-to-background ratio began to decrease. Annealing in an open system, such as in vacuum or under inert gas, may cause both PtAs₂ and GaAs to decompose thermally to produce gas phase As species. Therefore, in this case, the PtGa thin film starts to become Ga rich and PtGa₂ and Pt₃Ga₇ are produced, which coexist with PtGa and GaAs. Fig. 5 shows XRD patterns of a sample of PtGa₂ on GaAs heated to 100°C, 300°C, 450°C and 500°C, respectively, along with the pattern of an as-deposited film. The diffraction patterns for the sample were essentially identical up to 400°C. A new peak corresponding to the Pt₃Ga₇ (322) reflection begins to appear in XRD patterns of the sample annealed in the range of 450°C to 500°C. It is possible the PtGa₂ phase begins to react with extra Ga due to As evaporation from GaAs upon annealing.

Conclusions

Single phase thin films of Pt₂Ga, PtGa, and PtGa₂ have been successfully grown on GaAs by MBE. The results of annealing studies are in good agreement with the Pt-Ga-As ternary phase diagram. PtGa₂ and PtGa films are chemically stable on GaAs up to 450°C and 600°C, respectively. However, the Pt₂Ga films start




Fig. 3. XRD patterns of Pt_2Ga thin films on GaAs(100) for sample annealed to (a) $100^{\circ}C$, (b) $200^{\circ}C$, (c) $300^{\circ}C$, (d) $400^{\circ}C$ and (e) $500^{\circ}C$.

to react with GaAs even at temperatures of 200°C to produce PtGa, PtGa₂, Pt₃Ga₇ and PtAs₂ at temperatures of 500°C. It has been shown here that the thermodynamics of bulk materials can be used to control the chemistry at the metal/semiconductor interface. In order to understand the Pt-Ga intermetallic system further, several additional studies including annealing studies under As ambient, temperature dependent TEM and transport measuremeants of various intermetallic Pt-Ga phases grown by MBE still need to be carried out.




Fig. 4. XRD patterns of PtGa thin films on GaAs (100) for (a) the as-deposited film and after the sample was annealed to (b) 200°C, (c) 400°C, (d) 600°C, (e) 700°C and (f) 800°C.

This research was supported in part by the Office of Naval Research, the University of California MICRO program, and Hughes Air Craft Company. RSW would also like to thank the Henry and Camille Dreyfus Foundation for partial support.




Fig. 5. XRD patterns of PtGa₂ thin films on GaAs (100) for (a) the as-deposited film and after the sample was annealed to (b) 100°C, (c) 300°C, (d) 450°C and (e) 500°C.

References

- 1. L. J. Brillson, J. Phys. Chem. Solids 44, 703 (1983).
- 2. A. K. Sinha and J. M. Poate, in Thin Films-Interdiffusion and Reactions, edited by J. M. Poate, K. N. Tu and J. W. Mayor (Inter-science, New York, 1978), chap. 11.
- 3. L. J. Brillson, Surf. Sci. Rep. 2, 123 (1982).
- 4. C. T. Tsai and R. S. Williams, unpublished.
- 5. S. Kim, L. Hsu and R. S. Williams, Phys. Rev. B 36, 3099, (1987).
- 6. JCPDS, Powder Diffraction File: Inorganic Phases (1987). International Center for Diffraction Data.
- 7. E. Hellner and F. Laves, Z. Naturforsch., 2a, 1947, 177-183.
- 8. Young K. Kim, David K. Shuh, R. S. Williams, Larry P. Sadwick and Kang L. Wang, unpublished.

>-
۳.
2
=
Ξ
Ξ
CHEMISTRY
w
ਹ
ج
⊋
SURFACE
S
-0
=
<
Ħ
SOLID STATE
ρ
Ξ
0
S
Ħ
=
LIST.
>
5
Ξ
5
801
RIBUT
TRIBUT
STRIBUT
DISTRIBUT
DISTRIBUTION
RSTRACTS DISTRIBUT

TECHNICAL REPORT DISTRIBUTION LIST, GENERAL

DL/1113/89/1

Dr. Mark Johnson Dr. R.E. Smalley Department of Chemistry Ank University, Box 1892 White University, Box 1892 Houston TX 77251
Dr. Sylvia M. Johnson Dr. G.A. Somorjai SRI International Chemistry Dept. 333 Ravenswood Avenue University of California Mento Park, CA. 94025 Berkeley, CA. 94720
Dr. Z.H. Kafafi Optical Sci. Div., Code 6551 Naval Research Laboratory Washington, DC 20375-StrXI Saft Lake City, UT 84112
Dr. George H. Morrison Dr. Galen D. Stucky Chemistry Dept. Cornell University of California University of California Santa Barbara, CA 93106
Dr Daniel M. Neumark Dr. H. Tachikawa Chemistry Drivattiont Chemistry Dept. University of Salifornia Jackson State University Berkeley, CA 94720 Jackson, MI 39217
Dr. D. Ramaker Chemistry Dept. Surface Science & Technol Lab George Washington Univ. University of Maine Washington, DC 20052 Orono, ME 04469
Dr. R. Reeves Dr. R. P. Van Duyne Chemistry De at. Renselaer Polytech Inst. Northwestern University Troy, NY 12181 Evansion, IL. 60201
Dr. David M. Walba Microelectronics Center Chemistry Department Research Trangle Park University of Colorado No. Carolina. 27709 Boulder, CO 80309-0215
Dr. G. Ruboff BM Waison Research Ctr. PO Box 218 Vorkiown Hgis, NY 10598 Minneapolis, MN 55455
Dr. Richard J. Saykally Dr. B.R. Weiner Chemistry Department Department of Chemistry of California University of Puerto Rico Berkeley, CA 94720 Rio Piedras, PR 00931
Dr. Robert W. Shaw US Army Research Office Chemistry Department Box 12211 University of California Res. Triangle Park, NC 27709 Los Angeles, CA 90224
Dr. S. Sibener James Franck Institute Dr. R. Stanley Werfflms Dept of Chemistry University of Chicago University of California Chicago, II. 60637